



SHUTTERMAX[®] *Plus*

MAXimum Security, Speed, Insulation and Whisper-Quiet Operation

The European designed **SHUTTERMAX[®] Plus** is perfect for external applications where security and high speed operation is needed. The insulating properties of the individual slats provide temperature control to reduce energy consumption while providing whisper-quiet operation.

AUSTRALIAN MADE
EUROPEAN DESIGNED
GERMAN DRIVE TECHNOLOGY



Insulated Slat – front view



Compact side guide design



Insulated Slat – back view



GFA Safedrive®



Technical Datasheet – <i>SHUTTERMAX® Plus</i>		
Application	External/Internal	
Dimension	Max width	6000mm
	Max height	6500mm
Opening Speed	Up to	1.7m/sec
Closing Speed		0.7m/sec
Door Curtain	Anodised Aluminium external profile bonded to a hardened PVC longitudinal profile filled with polyurethane foam	Standard
Door Frame	Galvanised Steel	Standard
	Powdercoated	Optional
Top Roll Tube	Galvanised Steel	Standard
Guide System	Hardened PVC profile end guides and guide rails	Standard
Drive System	GfA Safedrive® with integrated safety brake & soft start/soft stop	Standard
Safety	Safedrive® integrated safety brake	Standard
	Door-line Safety Light Curtain (1800mm active)	Standard
	Bottom Profile “Soft-touch” reversing edge	Standard
	Emergency Stop Button	Standard
	Manual Chain Over-ride	Standard
Thermal Insulation	$U = 0.875 / R = 1.14$	23mm Profile
Acoustic Insulation	16 dB (calculated value – untested)	Standard (size dependant)
Wind Load Rating	Gusts > 120km/hr (Class 3)	Standard (size dependant)



MAX Door Solutions Pty. Ltd.

P: 1300 793 378

sales@maxdoors.com.au

56 Export Drive, Molendinar, QLD, 4214

PO Box 777, Biggera Waters QLD, 4216

www.maxdoors.com.au